

Parasound Halo JC3 Jr. spesifikasjoner

- Frequency Response:
- 20-20Khz, +/- 0.2dB
- Total Harmonic Distortion
- < 0.02% at 1 kHz
- Signal to Noise Ratio, 40 dB Setting >85dB, input shorted, IHF A-weighted
- >80dB, input shorted, unweighted
- Signal to Noise Ratio, 50 dB Setting
- >89dB, input shorted, IHF A-weighted
- >84dB, input shorted unweighted
- Signal to Noise Ratio, 60 dB Setting
- > 94dB, input shorted, IHF A-weighted
- > 91dB, input shorted, unweighted
- Inter-channel Crosstalk
- >80 dB at 1 kHz
- Input Impedance
- MM or MI: 47k Ω
- MC Variable: 50- 550 Ω
- Output Impedance
- Unbalanced: < 100 Ω
- Balanced: < 100 Ω per leg
- Input Capacitance
- 150 pF Input
- Sensitivity at 1 kHz, 4mV Input
- 40 dB: 4 mV for 450mV output
- 50 dB: 4 mV for 1.4 Volts output
- 60 dB: 4 mV for 4.25 Volts output
- Input Sensitivity at 1 kHz, 1V Output
- 40 dB: 9 mV for 1.0 Volt output
- 50 dB: 3 mV for 1.0 Volt output
- 60 dB: 0.9 mV for 1.0 Volt output
- Total Gain
- 40 dB / 50 dB / 60 dB (unbalanced output)
- 46 dB / 56 dB / 66 dB (balanced output)

- XLR Pin Identification
- 1 = Ground (Shield)
- 2 = Positive
- 3 = Negative (Return)
- AC Power Requirement
- Standby: <1 watt
- Power On: 9 watts
- 115 VAC or 230 VAC 50 – 60 Hz
- Dimensions
- Width: 17-1/4" (437mm)
- Depth: 14-3/4" (375mm) Depth with cables: 17" (432mm)
- Height: 2-1/2" (63.5mm)
- Height, without feet: 1-3/4" (45mm)
- Weight Net: 13 lbs. (5.9 Kg)
- Shipping: 19 lbs. (8.6 kg)