

Spesifikasjoner for Parasound Halo JC 5

- Power Output – Both Channels Driven
- 400 watts x 2, 8 Ω
- 600 watts x 2, 4 Ω
- Power Output – Bridged Mode
- 1200 watts x 1, 8 Ω
- Bridged 4 Ω operation is not recommended
- Power measurement parameters are at 120 VAC:
- 0.05% THD, RMS continuous power, full audio band (20 Hz – 20 kHz)
- Current Capacity
- 90 amps peak, per channel
- Slew Rate
- > 130 volts per microsecond
- Frequency Response
- 5 Hz – 100 kHz, +0/-3 dB
- 20 Hz – 20 kHz, +0/-0.25 dB
- Total Harmonic Distortion (THD)
- < 0.05 % at full power
- < 0.03 % at typical listening levels
- IM Distortion
- < 0.04 %
- TIM
- Unmeasurable
- Inter-channel Crosstalk
- > 87 dB at 1 kHz
- > 72 dB at 20 kHz
- Input Impedance
- Unbalanced: 33 k Ω
- Balanced: 66 k Ω , (33 k Ω per leg)
- Total Gain
- 29 dB Input
- Sensitivity for 28.28 V Output into 8 Ω
- Unbalanced: 1 V
- Balanced: 1 V per leg

- S/N Ratio
- > 116 dB, input shorted, IHF A-weighted
- > 111 dB, input shorted, unweighted Damping Factor
- > 1200 at 20 k Hz DC
- Trigger Requirements
- +9 Vdc to +12 Vdc, 5 mA
- Audio Trigger Requirements
- 2 mV – 10 mV
- XLR Pin Identification
- 1 = Ground (Shield)
- 2 = Positive
- 3 = Negative (Return)
- Dimensions
- Width: 17-5/8" (448 mm)
- Height without feet: 7-1/8" (181 mm)
- Height with feet: 7-3/4" » (197 mm)
- Depth: 20" (508 mm)
- Depth with cables: 21-1/2" (546 mm) Net Weight
- 73 lb. (33.1 kg) Shipping Weight
- 90 lb. (40.8 kg)
- Power Requirement
- Standby: 1 Watt
- Idle (no music playing): 225 Watts
- Typical listening levels: 400 Watts
- Maximum: 1500 Watts