

Spesifikasjoner Parasound Zonemaster 2

Power Output – RMS, Both Channels Driven (20 Hz - 20 kHz)

120 watts x 2 @ 8Ω

150 watts x 2 @ 4Ω or 2Ω

Minimum Speaker Impedance:

A+B Outputs of a Single Channel: 2 Ω

Note: Continuous operation at this minimum impedance might require additional ventilation for the amplifier.

Frequency Response:

20 Hz - 20 kHz, +0/-0.25 dB

5 Hz - 50 kHz, +0/-3 dB

Total Harmonic Distortion:

< 0.05 % at typical listening levels

< 1.0% at full power

Interchannel Crosstalk: 70 dB at 20 kHz

Total Gain: 29 dB (Level controls set to Maximum)

S/N Ratio: >112 dB, input shorted, IHF A-weighted

DC Trigger Requirements: +9 Vdc to +12 Vdc, 5 mA

Audio Trigger Requirements: 2 mV audio signal

Low Pass Crossover: 80 Hz, 18 dB per octave

AC Power Requirement:

300 Watts maximum

30 Watts typical (music playing)

15 Watts idle (no music playing)

0.5 Watts in standby

100-250 VAC 50/60 Hz (automatic)

Dimensions:

Width: 8.5" (220 mm)

Depth: 10" (254 mm)

Depth: 12" (305 mm) with AC cord and cables connected

Height, with feet: 2" (51 mm)

Height, without feet: 1.75" (45 mm), 1U

Weight:

Net: 4.3 lbs. (2.0kg)

Shipping: 7.3 lbs. (3.3 kg)